

# HD331A



Hotel/hospitality features



DECT handset



Anti-bacterial housing



HD audio

## Wireless flexibility for the hotel and guest sector

The Snom HD331A is an analogue, slim-designed hotel/guest room phone that offers users the greatest possible freedom of movement with its cordless DECT handset. GDPR-compliant by design, it offers the most important features of a hotel phone such as speed dial buttons, hands-free calling, hold and mute. If required, it can be expanded with up to 3 additional Snom

HD3 type DECT handsets. The antibacterial housing protects against germs and is easy to clean. The large, optical LED call and message indicator as well as the individual labelling options complete the overall picture of an attractive room phone.

## Basics and equipment

- Product information
  - Analog guest room phone | Cordless DECT handset | PN 00007033
  - Colour: gunmetal black and black
  - Anti-bacterial housing
- Equipment
  - Sturdy, solid construction
  - Customizable handset accent piece for color or branding opportunities
- Placement: indoor, desktop, nightstand

## Dimensions and weight

- Dimensions (H × W × D, approx.)
  - Cordless DECT handset on the base cradle  
216 mm × 82 mm × 110 mm
- Weight (approx.)
  - Cordless DECT handset on the base cradle:  
500 g

## Indicators and keys

- 7 LED indicators
  - Cordless DECT handset
    - Flash/Talk key indication: 1 red LED
    - Mute status indication: 1 red LED
    - Speakerphone mode: 1 red LED
    - Hold status indication: 1 red LED
    - Low battery indication: 1 red LED
  - Telephone base
    - Call status indication | Message waiting indication (MWI): 1 red LED
    - Charging indication: 1 red LED

- 31 hard keys in total
  - Cordless DECT handset
    - 12 keys (standard ITU telephone keypad), backlit
    - 4 dedicated audio keys
      - Speakerphone (with red LED)
      - Mute (with red LED)
      - Volume + / - (rocker)
    - 3 programmable function keys: Speed dialling
    - 5 dedicated function keys
      - Offhook (with red LED)
      - Onhook / Cancel
      - Hold (with red LED)
      - Message
  - Telephone base
    - 1 dedicated function key
    - Handset localisation

## Interfaces and connections

- Power options
  - Telephone base
    - Power adapter: 6 V
  - Cordless DECT handset
    - Battery (CORUN) lithium-ion, 3.7 V, 1000 mAh, removable, rechargeable, up to 7 h talk time, up to 168 h standby time, up to 11 h charging time
- Wired interfaces
  - Power adapter: coaxial power connector (socket)
  - Network connectivity (PABX): RJ11-6P4C socket
- Wireless interfaces
  - Handsets: DECT

## Audio devices and features

- Cordless DECT handset
  - Microphone
  - Handset earpiece
  - Hearing aid compatible (HAC)
- External speaker
  - Speakerphone mode

## DECT technology and features

- Standard: DECT
  - Handsets: up to 4 total
  - Wideband audio
- Frequency band
  - EU & UK & AU: 1,881.792 - 1,897.344 MHz
- Easy registration to compatible base stations

## Call features

- Quick call answer (by simple pick-up from the base/charger)
- Speed dialling via function keys
- Mute microphone (via dedicated function key)
- Speakerphone mode (via dedicated function key)

- Hold (via dedicated function key)

## Interoperability

### Environmental conditions

- Operating ambient temperature
  - 5 °C - +45 °C
- Humidity (non-condensing):
  - 5 % - 95 %

## Package contents

- Hardware
  - Telephone base
  - Cordless DECT handset
  - Power adapter
  - Battery
- Documentation
  - [Quick Installation Guide](#)

## Snom accessories and compatible devices

- DECT handset & charging cradle<sup>1</sup>
  - Up to 3 × [HD3 \(PN 00007011\)](#)
- Battery PN 00004627

## Series overview



HD30L<sup>1</sup>



HD300<sup>1</sup>



HD331<sup>1</sup>



HD350W<sup>1</sup>



HD351W<sup>1</sup>



HD3

<sup>1</sup> Also available as analogue model

## Disclaimer

Further information: [Snom HD331A webpage](#) | [Snom Service Hub](#) | [Type approval](#) | [Warranty information](#) | [Company locations](#)

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.